



All O/C dimensions use 2 m spacers and SS connector

	Actual Glass Size
A	69.812
B	67.865
C	65.342
D	62.342
E	59.342
F	57.812
G	55.865
H	53.342
I	51.812
J	49.865
K	47.342
L	44.342
M	41.342
M2	38.342
N	35.342
N2	32.342
O	29.342
P	23.342
Q	17.342
R	11.342

o/c w/Invisi	o/c w/Vista	o/C W/ 4 X 4	O/C W/ 6 X 6	Inside to Inside Post
72.033	73.962	75.312	77.312	71.722
70.086	72.015	73.275	75.275	69.775
67.563	69.492	70.752	72.752	67.252
64.563	66.492	67.752	69.752	64.252
61.563	63.492	64.752	66.752	61.252
60.033	61.962	63.222	65.222	59.722
58.086	60.015	61.275	63.275	57.775
55.563	57.492	58.752	60.752	55.252
54.033	55.962	57.222	59.222	53.722
52.086	54.015	55.275	57.275	51.775
49.563	51.492	52.752	54.752	49.252
46.563	48.492	49.752	51.752	46.252
43.563	45.492	46.752	48.752	43.252
40.563	42.492	43.752	45.752	40.252
37.563	39.492	40.752	42.752	37.252
34.563	36.492	37.752	39.752	34.252
31.563	33.492	34.752	36.752	31.252
25.563	27.492	28.752	30.752	25.252
19.563	21.492	22.752	24.752	19.252
13.563	15.492	16.752	18.752	13.252

ANYPOST Inside to Inside Lite 10	O/C Vista with Lite 10 Con
70.47	72.71
68.523	70.763
66	68.24
63	65.24
60	62.24
58.47	60.71
56.523	58.763
54	56.24
52.47	54.71
50.523	52.763
48	50.24
45	47.24
42	44.24
39	41.24
36	38.24
33	35.24
30	32.24
24	26.24
18	20.24
12	14.24